

## FETS

### 高温波纹管

Corrugated conduit

+200°C +392°F  
-80°C -112°F

Material: ETFE



- 产品由高技术聚合材料 ETFE 制成
- 良好的动态抗疲劳性能
- 优异的耐化学品性能
- 优异的耐候性能
- 广泛适用于各种有耐高温要求的场合
- HIGHTECH polymer material ETFE
- good dynamic fatigue strength
- excellent chemical resistance characteristics
- excellent weathering performances
- suits for extensive applications areas with high temperature requirements

温度范围 / Temperature range  
弯曲性能 / 柔韧性 / Flexibility/Ductility  
动态性能 / Dynamic  
机械防护性能 / Mechanical protection  
防火性能 / Fire precaution performance  
耐化学品性能 / Chemical resistance  
耐候性 / Resistance to weathering

min.					max.



产品号 Part No. <sup>1)</sup>	名义尺寸 Nominal width	波型 Profile <sup>2)</sup>	尺寸 Dimensions in mm (nom.) <sup>3)</sup>		弯曲半径 Bending radius in mm	包装单元 PU
			ID	外径 / OD		
黑色 / black	NW				stat. R.	m
FETSX-07B.50	07	X	7,0	9,8	15	50
FETSX-10B.50	10	X	9,9	13,0	25	50
FETSX-12B.50	12	X	12,5	16,0	35	50
FETSX-17B.50	17	X	16,8	21,5	40	50
FETSX-23B.50	23	X	23,8	28,8	45	50
FETSX-29B.25	29	X	27,8	32,5	55	25
FETSX-36B.25	36	X	36,4	42,7	60	25
FETSX-48B.25	48	X	47,4	54,4	70	25

您可以通过以下地址查询更多的技术信息 / You can find more technical information here

CADENAS – 产品CAD数据目录 / eCATALOG solutions electronic CAD catalog: <https://fraenkische-ip.partcommunity.com>

<sup>1)</sup> FIPHEAT® 波纹管编码规则 / Part numbering key for FIPHEAT® corrugated conduits: [www.fraenkische-ip.com/fipheat-part-no](http://www.fraenkische-ip.com/fipheat-part-no)

<sup>2)</sup> 波纹管波型 / Conduit profiles: [www.fraenkische-ip.com/fipsystems-profiles](http://www.fraenkische-ip.com/fipsystems-profiles)

<sup>3)</sup> 英制尺寸转换 / Conversion to inch: [www.fraenkische-ip.com/fipsystems-conversion-inch](http://www.fraenkische-ip.com/fipsystems-conversion-inch)

# FETS 产品性能 / Product performances

应用性能 <i>Application performances</i>	特性 <i>Characteristics</i>	单位 <i>Unit</i>	规范标准 <i>Standards, specifications</i>	备注 <i>Remark</i>
温度范围 / <i>Temperature range</i>	-80 到 / <i>to</i> +200 -112 到 / <i>to</i> +392	°C °F	IS FIP	
填充率(最大) / <i>Filling ratio (max.)</i>	70	%	IS FIP	推荐值 / <i>recommendation</i>
<b>防火性能 / <i>Fire safety performances</i></b>				
不含卤素和镉 / <i>Free from halogens and cadmium</i>	否 / <i>no</i>			
阻燃等级 / <i>Fire classification</i>	V0		UL 94	
<b>耐候性 / <i>Weathering performances</i></b>				
UV- 及耐候性能 <i>UV and weathering performance</i>	优异 <i>excellent</i>		IS FIP	>50 年 > <i>50 years</i>

测试条件参照EN ISO 139 , 温度 23°C / 湿度50% r. h. (如未注明测试条件). IS FIP = FIP内部测试规范  
*Tests carried out acc. EN ISO 139 at 23°C / 50% r. h. (if not indicated differently). IS FIP = Internal Specification FIP*

我们尽我们的知识水平所提供的数据, 图片和技术规格图档反映了当前的工程技术水平。这并不包含对最后应用有关的任何责任。产品用户需根据应用要求自行进行评估。以确定产品是否符合特殊应用条件。我们对产品的责任只考虑一般规定条件下的水平。FIP保留对产品数据和数值进行技术调整的权利。例如更改材料和加工工艺, 在保证产品性能数值不下降的情况下不会另行通知。

*The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.*