



NPPA-PG

+100°C || -40°C

+212°F -40°F

螺纹塞

Screw plug

材料: 尼龙玻纤增强 Material: polyamide glass fibre reinforced



- 螺纹塞
- ■用于封闭PG制螺纹孔的塞子
- screw plug nut
- for PG thread holes which need to be closed

温度范围 / Temperature range

UV保护性能 / UV protection

低温性能 / Cold environment performance

机械强度 / Mechanical strength












产品号 Part No. ¹⁾	螺纹尺寸 Thread size	尺寸 Dimensions in mm			重量 Weight	包装单元 PU
灰色 / grey	NW	ØA	С	D	g	↑ / Pcs
NPPA-P07G	PG07	15,0	8,0	6,0	0,7	10
NPPA-P09G	PG09	19,0	9,0	6,0	1,2	10
NPPA-P11G	PG11	22,0	10,5	7,0	1,7	10
NPPA-P13G	PG13,5	25,0	10,0	6,5	2,2	10
NPPA-P16G	PG16	27,0	10,0	6,5	2,3	10
NPPA-P21G	PG21	33,0	12,0	8,0	4,2	10
NPPA-P29G	PG29	44,0	12,0	8,0	5,4	10
NPPA-P36G	PG36	55,0	15,0	10,0	10,1	10
NPPA-P48G	PG48	69,0	17,0	12,0	23,3	10



您可以通过以下地址查询更多的技术信息 / You can find more technical information here

CADENAS - 产品CAD数据目录 / eCATALOGsolutions electronic CAD catalog: https://fraenkische-ip.partcommunity.com

1) FIPLOCK® 附件编码规则 / Part numbering key for FIPLOCK® accessories: <u>www.fraenkische-ip.com/fiplock-accsy-part-no</u>







NPPA-PG 产品性能 / Product performances

应用性能 Application performances	特性 Characteristics	单位 Unit	规范标准 Standards, specifications	备注 Remark				
温度范围 / Temperature range	-40 到 / <i>to</i> +100 -40 到 / <i>to</i> +212	°C °F	IS FIP					
防火性能 / Fire safety performances								
不含卤素和镉 / Free from halogens and cadmium	是 / yes							
阻燃等级 / Fire classification	НВ		UL 94					
火焰蔓延 / Spread of fire	非火焰蔓延 non flame propagating		IEC EN 61386					
耐候性 / Weathering performances								
UV- 及耐候性能 UV and weathering performance	非常好 very good		IS FIP	15 到 20 年 15 to 20 years				

测试条件参照EN ISO 139 , 温度 23°C / 湿度50% r. h. (如未注明测试条件). IS FIP = FIP内部测试规范 Tests carried out acc. EN ISO 139 at 23°C / 50% r. h. (if not indicated differently). IS FIP = Internal Specification FIP

我们尽我们的知识水平所提供的数据,图片和技术规格图档反映了当前的工程技术水平。这不包含对最后应用有关的任何责任。产品用户需根据应用要求自行进行评估。以确定产品是否符合特殊应用条件。 我们对产品的责任只考虑一般规定条件下的水平。FIP保留对产品数据和数值进行技术调整的权力。例如更改材料和加工工艺,在保证产品性能数值不下降的情况下不会另行通知。

The provided data, images and technical specification drawings reflect the current engineering level and are to the best of our knowledge. This does not include any liability regarding the final application. Users of the products have to make their own evaluation to determine the suitability for a specific application. Our liability for these products considers the stated level within our General Conditions only. FRAENKISCHE Industrial Pipes (FIP) reserves the right to adjust specified data and values as well as implementing technical adjustments of the products e. g. change of materials and processing technologies without prior notice as long as the specified values are not reduced.

FRÄNKISCHE Industrial Pipes GmbH & Co. KG / Hellinger Str. 1 / 97486 Königsberg/Germany Phone +49 9525 88-0 / Fax +49 9525 88-155 / info@fraenkische-ip.com / www.fipsystems.com